

Hello,

We are very pleased to present the following machine for your review and approval:

2006 CLAUSING CV1660

Geared Head Engine Lathe

Swing Over Bed Ways: 16"
Swing in Removable Gap: 27-1/2"
Swing Over Cross Slide: 10"
Distance Between Centers: 60"
Spindle Bore (Hole Thru Spindle): 4-1/8"
Spindle Bearings: Gamet
Spindle Nose: D1-8 Camlock
Spindle Speeds (16): 26 to 1700 RPM
Feed Range
Longitudinal: .044 to 1.48 mm/Rev.
Cross: .022 to 0.74 mm/Rev.
Thread Range
Inch (47): 7/16 to 80 TPI
Metric: 0.35 to 80 MM
Cross Slide Travel: 13-3/4"
Longitudinal Rapid Traverse Rate: 5 mm/min.
Cross Travel Rapid Traverse Rate: 2.5 mm/min.
Taper in Tailstock: #5 MT
Tailstock Quill Travel: 6"

-EQUIPPED WITH-

12" 3-Jaw Chuck with 2-Piece Reversible Hard Top Jaws
Telescopic Taper Attachment
Threading Dial
Inch/Metric Universal Gear Box
Rapid Traverse to the Carriage & Cross Slide
Full Length Rear Splash Guard
Coolant System
Motor and Controls: 10 HP 3/60/230-460 Volt AC- Currently Wired for 460 Volt Operation
Coolant Motor: 1/5 HP
Floor Space: 123" L-R x 46" F-B x 50" High
Weight: 5,500 Lbs. (Approx.)



PRICE.....\$17,500

Best Regards,

Mike Heim - Sales Manager



Two Spade Machinery LLC
Mobile: (207) 300-3649
Email: mike@2spade.com



