

Hello,

We are very pleased to present the following machine for your review and approval:

## 2007 Welltec 2200 F2R Injection Molding Machine

Barrel/Screw Size: 180 mm  
Theoretical Shot Volume: 17,177 cc  
Shot Weight: 545 oz  
Length/Diameter Ratio: 19.5  
Injection Pressure: 1,260 Kg/sq-cm  
Injection Rate: 2,529 cu-cm/sec  
Plasticizing Capacity: 915 kg/hr  
Injection Stroke: 675 mm  
Max Screw Speed: 57 rpm  
Injection Unit Force: 285 kn  
Carriage Stroke: 1,080 mm  
Clamping Force: 2,200 ton  
Max Daylight: 3,700 mm  
Clamping Stroke: 1,900 mm  
Distance Between Tie Bars: 1,600 mm x 1,600 mm  
Min Mould Dimension: 1,260 mm x 1,100 mm  
Mould Thickness Range: 900 - 1,800 mm  
Ejector Force: 385 kn  
Ejector Stroke: 450 mm  
Number of Ejector Pins: 33  
Main Motor: 225/165 hp/kw  
Number of Motors: 2  
System Pressure: 160 kg/sq-cm  
Hydraulic Pump Capacity: 892 l/min  
Number of Hyd Pumps: 2  
Number of Heater Zones: 5+1  
Heater Input Power: 67.54 kw  
Net Weight: 169 ton  
Oil Tank Capacity: 2,150 l

### -EQUIPPED WITH-

Yushin Netliner VN 11-EA-2000S Robot Loader  
B and R Processor



PRICE.....\$269,500

Best Regards,

Mike Heim - Sales Manager



*Two Spade Machinery LLC*  
*Office: (860) 356-4439*  
*Mobile: (207) 205-4761*  
*Email: mike@2spade.com*



