Hello,

We are very pleased to present the following machine for your review and approval:

2010 Haas SL-10

CNC Turning Center



Max Swing Over Bed: 16.25"
Max Swng Over Saddle: 8"
Max Turning Diameter: 11"
Max Turning Length: 14"
Spindle Speeds: 6,000 Max RPM
Spindle Drive: 15 HP
Hole Thru Spindle: 2.31"
Spindle Nose: A2-5
Hole Thru Draw Tube: 1.81"
Turret Capacity: 12 Station
Turret Travels (X,Z): 6.25" x 14"
Rapid Traverse Rate (X/Z): 1,200 IPM
Turret Index Time: 1 Second (Per 1 Tool)
Tailstock Quill Diameter / Taper: #3MT
Tailstock Quill Travel: 4.0" Hydraulic Travel
Max Bar Capacity: 1.75"
Max Swing Over Front Apron: 16.25"
Max Swing Over Cross Slide: 8"
Rapid Traverse Rate: 710 IPM

-EQUIPPED WITH-

Haas CNC Control
Chip Auger
Tailstock
Tool Presetter

PRICE.....$17,000

Best Regards,

Mike Heim - Sales Manager

Two Spade Machinery LLC
Mobile: (207) 300-3649
Email: mike@2spade.com


POWER ON
POWER OFF
EMERGENCY STOP
HANDLE JOG
CYCLE START
FEED HOLD
RESET
DISPLAY
CURSOR
OVERRIDES


SL
10
TAIL STOCK
TOOL PRESETTER
DANGER
WARNING
We're Here To Help You
888-917-4227


Mobil Vactra Oil No. 2




HAAS
MODEL
SL-10
HAAS AUTOMATION, INC, OXNARD, CA. 93030
SERIAL NUMBER 3086539
DATE OF MFG 07/10
VOLTAGE 195-260
PHASE 3
HERTZ 50/60
FULL LOAD ..... 40 AMPS
LARGEST LOAD ..... 35 AMPS
SHORT CIRCUIT INTERRUPTING CAPACITY - 10,000 AMPS
WIRING DIAGRAM 96
SHORT CIRCUIT CURRENT 5,000 Amps RMS SYMMETRICAL
ARC FLASH RATING: 208-240VAC MODELS HRC-1,
360-480VAC MODELS HRC-2.
NEMA TYPE 1 ENCLOSURE-FOR INDOOR USE ONLY.
OVER CURRENT PROTECTION PROVIDED
AT MACHINE SUPPLY TERMINALS.
MADE IN U.S.A.
P/N 29-10049




C1