

Hello,

We are very pleased to present the following machine for your review and approval:

## 2012 WA Whitney 3400H

### CNC Plasma Punch Combo

Punch Tonnage Capacity: 55

Maximum Cutting Capacity

(Edge Start Mild Steel): 2.5"

Max Punch Diameter: 5"

Minimum Material Thickness: .060"

Maximum Material Thickness: .75"

Max Positioning Area (X Axis): 190.6"

Max Positioning Area (Y Axis): 80.7"

Nominal Blank Size

(Without Aux. Tables): 80" x 160"

Extended Blank Size

(With Aux. Tables and Repositioning): 80" x 320"

Positioning Speed Per Axis: 1,200 in/min

Positioning Accuracy:  $\pm 0.005"$

Max Material Weight: 3,000 Lbs.

### -EQUIPPED WITH-

Siemens Sinumerik Controller

55 Ton Hydraulic Punch

Hypertherm HPR260 XD Plasma Source

Plate Partner Vacuum

Sheet Loading System with Anver

2,000 Lb Vacuum Lifter

Tooling



PRICE.....\$99,500

Best Regards,

Tobin Demos - General Manager



**Two Spade Machinery LLC**

Office: (802) 518-4161

Mobile: (802) 376-8157

Email: [tobin@2spade.com](mailto:tobin@2spade.com)





