

Hello,

We are very pleased to present the following machine for your review and approval:

2016 Southwestern Industries Trak TRL1630SX

CNC Tool Room Lathe

Height of Centers-8"
Distance between centers-30"
Swing over bed -16"
Swing over saddle wings-16"
Swing over cross slide-8.6"
Cross slide travel-9.6"
Tool section max-3 /4"
Coolant tank capacity-11 gal.
Width of Bed-12.6"
Height of Bed-12.6"
Spindle Nose (Camlock)-D1-6
Spindle through hole-2.12"
Spindle taper-MT#6
Taper in reduction sleeve -N/A
Spindle dia at front bearing-3.15"
Number of bearings-2
Bearing class (radial round)-P5
Spindle speed range (RPM)-150-2500
Optional Tailstock Quill travel-5"
Quill diameter-2.36"
Quill taper hole-MT#4
Spindle Motor HP -7.5
Power requirements, control-110V; 1P; 8 A
Power requirements, machine-220V;3P;60Hz

Amps full load current-25, Dimensions net - 79 x 38 x 54", Dimensions shipping - 87 x 45 x 67"

Weight net - 2,200 lbs., Weight shipping - 2750 lbs., Maximum rapid feed X - 100

Maximum rapid feed Z - 150, Coolant pump motor -1/8 HP, Spindle motor brake - Dynamic braking

Way surface hardness - 400 - 450 HB, Head stock lubrication - Oil bath

-EQUIPPED WITH-

Sliding door for easy set-ups, Bedways hardened and ground, Sliding surfaces Turcite coated
Dovetails on cross slide, V-ways on saddle, Adjustable saddle gibbs, Prototrak SLX Control
Collet Closure Attachment, 4 Way Quick Change Tool Post, 10" 3 Jaw chuck, Tail stock
Tool post only, no holders, 8 position gang tooling with mounting plate, Manuals

PRICE.....\$28,500

Best Regards,

Tobin Demos - General Manager



Two Spade Machinery LLC
Office: (802) 518-4161
Mobile: (802) 376-8157
Email: tobin@2spade.com







