

Hello,

We are very pleased to present the following machine for your review and approval:

2017 Crest COC8T-1014

Aqueous Ultrasonic Cleaning System

Item Features Tank Dimensions: 10" X 14" X 10" (8)
[Left to Right X Front to Back X Depth (Liquid Depth)]

Console Dimensions: 172" X 34" X 38"

[Left to Right X Front to Back X Height]

Overall Dimensions with CTS-250: 201" X 41" X 84"

[Left to Right X Front to Back X Height]

Process: Load, Wash, Rinse, Passivation,
Passivation, Neutralize, Rinse, Rinse, Dry, Unload

Station #1: Load

Chemistry: Station #2 and #3: Alkaline Detergent

Station #4: Nitric Acid (30% concentration)

Station #5: Citric Acid

Station #6: Sodium Bicarbonate

Station #7 and #8: Deionized water

Station #9 Dry

Station #10: Unload

The EMO circuit, when activated, shuts off all energy to the system

EXCEPT:

Main Disconnect switch

Industrial PC

PC monitor

Printer

Barcode Scanner

Electrical Box Fans

1TF 2kVA Transformer

120VAC Receptacle

Main Power indicator

Noise Filter (2 units)

24VDC 10A Power Supply - 1PW

Safety Relay

Current Metering Relay

PLC Power Supply à 2PW

PLC Power Supply à 3PW

Proface touch screen

24VDC 2.5A Power Supply à 4PW

Tower light with buzzer

Automation: Model CTS-250

Power Requirement 240Volts/3 phase/60Hz/59Amps

Work Flow: Left to Right

Facilities: 1-3 GPM (4-6 GPM on demand) DIW @ 1-2 Mohm, 30-35 psi and

process temperature, 65-70 CFM CDA @ 30 psi, 1-2 CFM shop air @ 60 psi,

unrestricted floor drain.

PRICE.....\$52,500

Best Regards,

Mike Heim - Sales Manager



Two Spade Machinery LLC

Mobile: (207) 300-3649

Email: mike@2spade.com





