

Hello,

We are very pleased to present the following machine for your review and approval:

2017 Okamoto OGM 1220 UIII

CNC Universal Cylindrical Grinder

Swing Over Table: 12.59"
Distance Between Centers: 19.69"
Max. Diameter to the Ground: 11.81"
Max Weight Between Centers: 330 lbs.
Grinding Wheel Size (O.D x Width x I.D):
14" x 1.5" x 5"
Wheel Head X-Axis Travel 11.81"
Wheel Head Swivel Angle: $\pm 30^\circ$
Wheel Head Least Travel Increment: 0.00001"
Wheel Head Continuous Feed Rate:
0.0001" - 157.48" per min.
Wheel Head Rapid Feed Rate: 157.48" per min.
Table Z-Axis Travel: 34.25"
Table Swivel Angle: 0° to -10°
Table Least Travel Increment: 0.00001"
Table Continuous Feed Rate:
0.0001" - 393.70" per min.
Table Rapid Feed Rate: 393.7" per min.
Work Head Center Taper: MT No.4
Work Head Spindle Speed: 10-500 min-1
Work Head Swivel Angle: 30° to -90°
Tailstock Spindle Stroke: 1.18"
Tailstock Center Taper: MT No.4
Motor Grinding Wheel Spindle: 7.3 HP
Motor Workhead Spindle: 1.0 HP
Approx. Dimensions: 144" X 79" X 68" H
Approx. Machine Weight 8,000 LBS.



-EQUIPPED WITH-

Okamoto/ Fanuc MDI Control
Swivel Table
Swivel Workhead
Universal Workhead
Coolant with Filtration

PRICE.....\$54,500

Best Regards,

Tobin Demos - General Manager



Two Spade Machinery LLC
Office: (802) 518-4161
Mobile: (802) 376-8157
Email: tobin@2spade.com

