

Hello,

We are very pleased to present the following machine for your review and approval:

2019 Machitech SILVERCUT HD

CNC Plasma Cutter

5ft x 10ft Table Size

CNC CONTROL:

Hypertherm Edge Connect

Windows based, 19" glass touch screen

2 USB port, network connection

Shape library

Part Program Support (PPS), Remote Help, Auto gas support, DXF import, and shape nesting

Hypertherm ProNest CAD/CAM Software

Input for Control is single phase 220v

GANTRY:

6" x 6" Steel

Clearance under gantry: 5"

Linear ways

½" Agma 10 rack and pinion

RAILS:

½" Agma 10 rack and pinion

Self-cleaning Dual Vee rails

Cutting Speed: 0 to 500 IPM

Max. Traverse Speed: 800 IPM

1 Plasma

HYPERTHERM XPR170 SOURCE:

Maximum open-circuit voltage: 360 VDC, Maximum output current: 170 A, Maximum output power: 35.7 kW Voltage: 50-210 VDC, 100% arc voltage: 210 V, Duty cycle rating: 100% at 35.7 kW, 40° C (104° F)

Ambient temperature range: -10° C-40° C (14° F-104° F), Power Requirements: 3 Phase, 480v.

Will include Step Transformer from 208-215v to 480v for free, Cooling: Forced air (Class F)

Insulation: Class H, EMC emissions classification (CE models only): Class A

Lift points: Top lift eye weight rating 454 kg (1,000 lb.), Bottom lift truck slots



PRICE.....\$49,900

Best Regards,

Mike Heim - Sales Manager



Two Spade Machinery LLC

Office: (860) 356-4439

Mobile: (860) 538-7814

Email: mike@2spade.com



