

Hello,

We are very pleased to present the following machine for your review and approval:

Okuma LB45II 3000M

CNC Turning Center

Swing Over Bed: 35.43"
Turning Diameter, Shaft Diameter: 21.65"
Machining Length: 118.11"
Distance Between Centers: 120"
Spindle Nose: A2-11
Spindle Bore Diameter: 5.12"
Spindle Speeds: 2400 RPM
Spindle Horsepower: 50 HP
X - Axis Travel: 17.32"
Z - Axis Travel: 120.47"
Rapid Traverse Rates: 591 IPM
Rapid Traverse Rates: 787 IPM
Turret Configuration: 12 V12 VDI Turret
Tailstock Quill Diameter: 5.12"
Tailstock Quill Travel: 6.69"
Tailstock Travel: 118"
Machine Weight: 39,600 LBS.



-EQUIPPED WITH-

120" Centers
Tool Presetter
Programable Tailstock
Live Tooling
Hydraulic Steady Rest
with 8" capacity (mfg by arobotech systems inc)
Chip Conveyor
Choice of 12" 3 Jaw SMW Autoblock Hydraulic Chuck
or 21" 3 Jaw Samchully
Hydraulic Chuck with 6.5" Through Hole

PRICE.....\$89,500

Best Regards,

Mike Heim - Sales Manager



Two Spade Machinery LLC
Office: (860) 356-4439
Mobile: (860) 538-7814
Email: mike@2spade.com



